

MATERIAL SAFETY DATA SHEET

350 RING ROAD ELIZABETHTOWN, KY 42701 (270) 769-5557 (270) 769-6418

GREEN HIGH STRENGTH RETAINING COMPOUND PART NO. 49476

SECTION I – IDENTITY INFORMATION

Product Type: Anaerobic Adhesive/Sealant

SECTION II – COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Component	CAS Number	<u>%</u>
P: 1 1 P:	25052 45 5	65.55
Dimethacrylate Ester	25852-47-5	65-75
Bisphenol A Fumurate Resin	39382-25-7	20-30
Saccharin	81-07-2	1-3
Polyethylene	9002-88-4	1-3
Amorphous Silica	112945-52-5	0.1-1.0
Cumene Hydroperoxide*	80-15-9	1-3
Organic Acid	Trade Secret	0.1-1.0
Dyes	Trade Secret	0.03-0.10

^{*}SARA Section 313 Toxic Chemical

Ingredients which have exposure limits

Exposure Limits (TWA)	ACGIH (TLV)	OSHA (PEL)	<u>OTHER</u>
Amorphous Silica TWA	10mg/m3 TWA	6mg/m3 TWA	3mg/m3 TWA resp. dust

SECTION III - HAZARDOUS IDENTIFICATION

Toxicity: Mild eye irritant

Primary Routes of Entry: Eyes, skin

Signs of Exposure: May cause dermatitis on prolonged contact in sensitive

individuals.

Existing Conditions

Aggravated by Overexposure: None known

SECTION IV – FIRST AID MEASURES

Ingestion: Do not induce vomiting. Keep individual calm. Obtain

medical attention.

Inhalation: Does not apply.

Skin Contact: Wash affected area with soap and water.

Eye Contact: Flush with warm water. Seek competent medical attention.

SECTION V - FIRE FIGHTING MEASURES

Flash Point: 150-200⁰ F, Tag Closed Cup

Extinguishing Media: Foam, Dry chemical or Carbon Dioxide

Unusual Fire or Explosion Hazards: None Special Fire Fighting Procedures: None

Hazardous Products formed by

Fire or Thermal Decomposition: Irritating Organic Vapors

SECTION VI – ACCIDENTAL RELEASE AND DISPOSAL MEASURES

Accidental Spill or Leak: Soak up with inert absorbent. Store in a partly filled,

closed container until disposal.

Disposal Procedures: Incinerate or dispose of in an approved landfill in

accordance with local and EPA regulations. Not a RCRA

hazardous waste

SECTION VII - HANDLING AND STORAGE

Safe Storage: Store below 100^0 F.

Handling: Avoid contact with skin and eyes.

SECTION VIII – PROTECTIVE EQUIPMENT

Ventilation: Does not apply. Respiratory Protection: Not applicable.

Skin: Rubber, polyethylene, or neoprene gloves. Eye Protection: Safety glasses or goggles with side shields.

SECTION IX – PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Green liquid

Odor: Mild Boiling Point: >300°F

Vapor Pressure: <5mmHg @ 20⁰ C

Vapor Density: Approximately 3 (Air = 1)

Evaporation Rate: N/A
Specific Gravity: 1.04
Solubility in Water: Negligible

SECTION X – STABILITY AND REACTIVITY DATA

Stability: Stable

Hazardous Polymerization: Will not occur

Incompatibility: None

SECTION XI – TOXICOLOGICAL INFORMATION

See section III

SECTION XII – ECOLOGICAL INFORMATION

No Data

SECTION XIII - TRANSPORTATION INFORMATION

Domestic Ground Transport

Proper Shipping Name: Unrestricted (not more than 450 liters)

Combustible Liquid, n.o.s. (more than 450 liters)

Hazard Class or Division: Unrestricted (not more than 450 liters)

Combustible Liquid (more than 450 liters)

Identification Number: None (not more than 450 liters)

NA 1993 (more than 450 liters)

Marine Pollutant: No

SECTION XIV - REGULATORY INFORMATION

CA Proposition 65: This product contains saccharin. Proper usage necessitates

no Proposition 65 warning.

SECTION XV – HAZARD CODE INFORMATION

<u>Hazard</u>	NFPA Hazard Code	HMIS Hazard Code
Health	1	1
Fire	1	1
Reactivity	1	1
Specific Hazard	None	Personal protection: See Section VIII

NFPA is a registered trademark of the National Fire Protection Association.

HMIS is a registered trademark of the National Paint and Coatings Association.

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. Because the information contained herein may be applied under conditions beyond our control, we assume no responsibility for its use.

Rev. 03/07/02