

TERMINAL SUPPLY CO. We've got it. We'll build it. We'll solve it.

Part Number

MX-M84455

Available mid to late September

LED Dome



244

- 9 LED's
- 12.8VDC
- AMP .4
- 2"Hx 2¾"L
- 450 Lumens
- Termination blade connector .25"
- 5 year manufacture warranty
- For use in Ford Transit van factory replacement

Part Number

MX-MWL-52

Surface Mount **Work Light**



- 8 LED's
- 11"L X 2"H
- **2,500 lumens**
- Black housing
- 2 hole surface mount
- 12/24VDC dual voltage
- 2.4A 12V/1.2A 24V
- **Polycarbonate** lens & aluminum housing
- Includes gasket and stand-off bracket
- 5 year warranty
- Connector: 2 jacketed leads blunt cut,11"

Part Number

MX-MWL-36-A

Adjustable Work Light

....II Maxxima

- 9 LED's
- 4,200 Lumens
- Replaces MWL-36
- Integrated On-Off switch
- 4 hole surface mount
- 4.6"W X 9.4"H X 3.2"D
- 3.6A 12V/1.8A 24V
- 5 year manufacture warranty
- Polycarbonate lens & aluminum housing
- Hardwired 11" pigtail with DT04 plug


Part Number	Replaces	Operating Voltage	Operating Temp.	Operating Life	Waterproof Level
LED-H11	H8 /H9 /H11	DC10-	-40°C - +90°C	>30000 Hrs.	IP68
LED-H13	H-1/ H9008L	24Volt			


DOT LED Bulb Headlight



LED-H11 works with:

- · 2005-2021 Ford (models: Ranger, Focus, Fusion, Edge, F-150, Escape, Expedition, Transit-150/250/350, etc.)
- 2009-2019 Dodge (models: Charger, Durango, Ram 1500/2500/3500, Grand Caravan, etc.)
- 2007-2021 GMC (models: Sierra 1500/2500HD/3500HD, Canyon, Yukon, Terrain, etc.)
- 2003-2021 Chevrolet (models: Silverado 1500/2500/3500, Tahoe, Malibu, SS, Sonic, Colorado, etc.)





- 2007-2020 Chevrolet (models: HHR, Cruze, Camaro, City Express, Spark EV, etc.)
- 2004-2014 Dodge (models: Durango, Ram 1500, Ram 2500, etc.)
- 2007-2012 Ram (model: XL-7, Dakota, etc.)





Fast cooling system with 12,000RPM speed super fan, rapid thermal diffusion.

WANT TO SEE MORE?



Ask for your copy of our brand new 500+ page Terminal Supply Co. catalog.

Part Number	Amp.	Color	
CBTT-5	5	Tan	
CBTT-7.5	7.5	Brown	
CBTT-10	10	Red	
CBTT-15	15	Blue	
CBTT-20	20	Yellow	
CBTT-25	25	White	
CBTT-30	30	Green	

- Operational temp: -40°C - 85°C
- Terminals: Tin plated copper alloy
- Voltage rating: 28VDC
- Body: Thermoplastic -(UL Rated 94-V-0)
- Not intended for submersible water application

Type III
Mini
Blade
Circuit
Breaker













Part Number	Coupler Gender	Body Size ISO	Body Size	Thread Size	Working Pressure
QC-FF10-F-06N	Female	10	3/8	3/8-18 NPT	5075
QC-FF10-M-06N	Male	10	3/8	3/8-18-NPT	5075
QC-FF12-F-08N	Female	12	1/2	1/2-14 NPT	5075
QC-FF12-M-08N	Male	12	1/2	1/2-14 NPT	5075
QC-FF19-F-12N	Female	19	3/4	3/4-14 NPT	5075
QC-FF19-M-12N	Male	19	3/4	3/4-14 NPT	5075

Flat Face Hydraulic Quick Couplers

- FF series ISO 16028
- Prevent fluid loss
 during disconnection
 and allow minimal inclusion
 of contaminants during connection
- Temp Rating: -40°F (-40°C) to 223°F (106°C)
- Material: Nitrile seals and are zinc nickel plated to prevent higher corrosion resistance
- A safety locking sleeve prevents accidental disconnection

Part Number

KL-935DAGL

Digital Level with Programmable Angles



Female



- Pre-programmed commonly used target pitches for efficiency and ease-of use: 1/8-Inch, 1/4-Inch, 3/8-Inch and 1/2-Inch per foot
- Easily achieve target angle by setting an audible alarm; LCD will change color as a visual indicator of reaching the set target angle
- Use in bullseye orientation to accurately determine X- and Y-axis
- Soft carrying case and 2 x AA batteries included
- Strong magnetic base attaches to ferromagnetic surfaces
- Display auto-rotates when used in horizontal or vertical orientation
- High visibility reverse contrast display improves visibility in dimly lit work environments
- V-Groove edges enable optimal alignment on conduit and pipes for bending and alignment



Male