



CYCLO[®] INDUSTRIES, LLC

MATERIAL SAFETY DATA SHEET

This MSDS is being provided to your company for the purpose of providing current health and safety information to your management and for your employees who work with this product. Please read the information on these sheets and then provide this information to those people at your company whose responsibility it is to comply with FEDERAL, STATE and COMMUNITY RIGHT TO KNOW regulations. Also, make this information available to any employee who requests it.

If Cyclo Industries, LLC considers the formula of this product to be a trade secret, the exact chemical names of the ingredient(s) and the percentages in which they are combined will not appear in the body of this sheet. The exact composition is available upon request to physicians, industrial hygienists and other health professionals.

SECTION 1 – PRODUCT & COMPANY IDENTIFICATION

Product Name: Rally[®] Performance™ Fast Oil™ Treatment, Stock No. 82400

Product Use: Improves acceleration, maximizes horsepower, reduces fuel consuming friction and drag.

Manufactured by: Cyclo Industries, LLC
10190 Riverside Drive, Palm Beach Gardens, Florida 33410-4881
Telephone: (561) 775-9600

First Aid Emergency: (800) 752-7869 or (312) 906-6194

Shipping Emergency: (800) 424-9300 or (703) 527-3887 (CHEMTREC)

SECTION 2 – COMPOSITION/INFORMATION ON INGREDIENTS

CAS Reg. No.	Material	Percentage	Exposure Limits
This product does not contain any hazardous ingredients.			

SECTION 3 – HAZARDS IDENTIFICATION

Effects of Overexposure:

Ingestion: Essentially nontoxic product may cause irritations.

Inhalation: Vapors of overheated product may cause irritations.

Skin Contact: On prolonged contact, irritation may occur.

Eye Contact: May cause irritation.

Carcinogenicity: NTP Carcinogen = No; IARC Monographs = No; OSHA Regulated = No

Health Hazards (Acute and Chronic): The polymer and mineral oil are acute, essentially non-toxic. Chronic effects are not known.

Medical Conditions Generally Aggravated By Exposure: None known.

SECTION 4 – FIRST AID MEASURES

First Aid Procedures:

Skin Contact: Wipe off excess, wash with soap and water.
 Inhalation: In case of inhalation of overheated product, move from source of exposure and inhale fresh air.
 Consult physician.
 Eye Contact: Immediately rinse eyes with eyelids retracted for at least 15 minutes with water. Consult physician.

SECTION 5 – FIRE FIGHTING MEASURES

Flash Point: 335°F (168°C) **Method Used:** COC

Flammable Limits in Air by Volume: Not determined

Extinguishing Media: Foam, dry chemical, water spray or carbon dioxide

Special Fire Fighting Procedures: Wear full protective fire gear including self-contained breathing apparatus with full face piece.

Unusual Fire and Explosion Hazards: Product of combustion includes fumes, smoke and carbon monoxide.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Spill/Leak Procedures: Report spills as required to appropriate authorities. On the ground, use sawdust, diatomaceous earth, scrape and remove.

SECTION 7 – HANDLING AND STORAGE

Handling & Storage Procedures: No special measures necessary. See product label for additional information. KEEP OUT OF THE REACH OF CHILDREN.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory Protection: Necessary only when handling overheated product. Use respirator with cartridge to remove organic chemical vapors.

Ventilation:

Local Exhaust Rate:	May be used
Special:	Not necessary
Mechanical (General):	May be used

Protective Gloves: PVC type

Eye Protection: Chemical worker goggles.

Work/Hygienic Practices: Eye washes and safety showers in the workplace are recommended.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: >395°F (>202°C)

Specific Gravity (H₂O=1): 0.88

Vapor Pressure (mmHg) at about 70°F: <<1

Vapor Density (Air=1): >1 (heavier than air)

Solubility in Water: Not soluble

pH: Not determined

Evaporation Rate (Butyl Acetate = 1): <<1 (slower)

Appearance and Odor: Clear pale yellow with low oily odor

Volatile Organic Compound (VOC) (as packaged minus water): Not determined

SECTION 10 – STABILITY AND REACTIVITY

Stability: Stable

Conditions to Avoid: Overheating of product, long term temperature limit 215° F.

Incompatibility (materials to avoid): Strong oxidizing agents.

Hazardous Decomposition or Byproducts: On overheating, irritating oil vapors are formed.

Hazardous Polymerization: Will not occur.

SECTION 11 – TOXICOLOGICAL INFORMATION

Toxicological Data: Long-term toxicological studies have not been conducted for this product. See Section 3 of this MSDS for acute symptoms of overexposure and carcinogenicity information.

SECTION 12 – ECOLOGICAL INFORMATION

Aquatic/Terrestrial Toxicity Environmental Fate No data is available at this time.

SECTION 13 – DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in accordance with local, state and federal regulations. Do not flush to drain. Before attempting clean up, refer to other sections of this MSDS for hazard caution information.

