

CYCLO[®] INDUSTRIES, LLC

MATERIAL SAFETY DATA SHEET

10190 Riverside Drive, Palm Beach Gardens, Florida 33410-4881
Phone: (407) 775-9600

In Emergency: (800) 752-7869 Ext. 10 (USA only)
Outside USA call collect 1 (312) 942-5969 Ext. 10

This MSDS is being provided to your company for the purpose of providing current health and safety information to your management and for your employees who work with this product. Please read the information on these sheets and then provide this information to those people at your company whose responsibility it is to comply with FEDERAL, STATE and COMMUNITY RIGHT TO KNOW regulations. Also, make this information available to any employee who requests it.

If Cyclo Industries, LLC considers the formula of this product to be a trade secret, the exact chemical names of the ingredient(s) and the percentages in which they are combined will not appear in the body of this sheet. The exact composition is available upon request to physicians, industrial hygienists and other health professionals.

SECTION 1 — PRODUCT IDENTIFICATION

Product Name: C-207 Cyclo[®] 100% Concentrate Windshield Cleaner & Anti-Freeze

Chemical Name: Methanol

Hazardous Material Description: Consumer Commodity ORM-D

NFPA Code: HEALTH=3 FLAMMABILITY=3 REACTIVITY=0

SECTION 2 — PHYSICAL DATA

Boiling Point: 148°F

Specific Gravity: 0.791 @ 20°F

Vapor Pressure: 96 mm HG @ 68°F

Vapor Density: 1.1

Solubility in Water: Complete

Evaporation Rate: Not applicable

Appearance and Odor: Blue liquid

SECTION 3 — HAZARDOUS INGREDIENTS

CAS Reg No.	Material	Percentage	Exposure Limits
67-56-1	**Methanol	80 - 100%	200 PPM (skin)* - OSHA 250 PPM (skin)* - ACGIH 200 PPM - TWA 250 PPM - STEL

* (skin) notation indicated that absorption through the skin can contribute significantly to overall exposure.

** This chemical is subject to the reporting requirements of SARA Title III Section 313 and the Pennsylvania Right To Know Hazardous Substance Survey.

SECTION 4 — FIRE AND EXPLOSION HAZARD DATA

Flash Point: 51.8°F (Closed Cup)

Auto Ignition Temperature: 725°F

Flammable Limits: Lower Explosion Limit: 6

Upper Explosion Limit: 36.5

Extinguishing Media:

Use halon, carbon dioxide, or alcohol foam. Water spray or fog can cool fire, but may not be effective in extinguishing the fire.

Special Fire Fighting Procedures:

Keep unnecessary people away, isolate hazard area and deny entry. Avoid breathing vapors, stay upwind. Wear NIOSH approved self-contained breathing respirator in the positive pressure mode and chemical protective clothing specifically recommended for methanol. Use halon or carbon dioxide extinguishers or alcohol foam for small fires. Water spray can cool fire, but may not be effective in extinguishing fire. Large fires should be extinguished with alcohol foam. Use water spray to cool containers exposed to fire. Stay away from ends of tanks. Containers may explode in heat of fire. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. Isolate for ½ mile in all directions if tank car or truck is involved in fire.

Unusual Fire and Explosion Hazards:

Dangerous fire and explosion hazard when exposed to heat or flame. Methanol is extremely flammable and forms explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back.

SECTION 5 — HEALTH HAZARD DATA

Effects of Overexposure:

Ingestion: Headache, weakness, drowsiness, lightheadedness, nausea, vomiting, drunkenness, irritation of the eyes and blurred vision. There is usually a latency period during which the acute symptoms may disappear, then relapse. Symptoms during the relapse include nausea, vomiting, dizziness and headache.

SECTION 5 — HEALTH HAZARD DATA continued

Inhalation: Headache, weakness, drowsiness, lightheadedness, nausea, vomiting, drunkenness, irritation of the eyes and blurred vision. There is usually a latency period during which the acute symptoms may disappear, then relapse. Symptoms during the relapse include nausea, vomiting, dizziness and headache.

Skin Contact: May defat the skin which can lead to dermatitis.

Eye Contact: Eye irritant.

Aggravated Medical Conditions:

Persons with existing skin, kidney, liver or eye disorders may be at increased risk when exposed to methanol. Methanol may enhance the toxicity of carbon monoxide.

Other Health Effects:

Chronic exposure to methanol can result in headache, dizziness, nausea, vomiting, weakness, vertigo, chills, unsteady gait, dermatitis, edema of the arms, gastric pain, insomnia, blurred vision, constricted visual fields, changes in color perception, double vision and blindness. Methanol has also been reported to cause shooting pains in the lower extremities and multiple neuritis, characterized by numbness and prickling on the skin and shooting pain in the back of the hands and forearms. Sleep disturbances and digestive problems may occur. Methanol is a defatting agent and can cause dermatitis.

Carcinogenicity: NTP=No; IARC Monographs=No; OSHA Regulated=No

First Aid Procedures:

- Ingestion: If the person is conscious, induce vomiting immediately. Then give 2 teaspoons of baking soda in a glass of water. DO NOT INDUCE AN UNCONSCIOUS PERSON TO VOMIT. Get medical attention immediately.
- Skin Contact: Promptly remove any contaminated clothing and wash the skin with soap and water. Systemic effects may be delayed by 18 to 72 hours, therefore, keep individual under observation.
- Inhalation: Move the exposed person to fresh air at once and call emergency medical care. If breathing has stopped, give artificial respiration. If breathing is difficult, give humidified oxygen.
- Eye Contact: Immediately wash the eyes with large amounts of room temperature water for at least 15 minutes occasionally lifting the lower and upper eyelids. Get medical attention immediately. A follow up visit to an ophthalmologist should be made. Contact lenses should not be worn when working with this chemical.

SECTION 6 — REACTIVITY DATA

Stability: Stable

Incompatibility (materials to avoid):

Strong oxidizing agents, aluminum, zinc or metals that displace hydrogen, rubber and rubber based coatings, chromic anhydride, lead perchlorate and perchloric acids.

SECTION 6 — REACTIVITY DATA continued

Hazardous Decomposition Products:

Excessive heating and/or incomplete combustion will produce carbon monoxide and toxic vapors such as formaldehyde.

Hazardous Polymerization: Will not occur.

SECTION 7 — SPECIAL PROTECTION INFORMATION

Respiratory Protection:

Do not use air purifying respirator. Use appropriate NIOSH approved supplied air or self contained respirator. Respirators must be selected based on airborne levels found in the workplace and must not exceed the working limits of the respirator.

Ventilation:

Provide local ventilation to maintain exposure levels below recommended exposure limits. Use explosion proof ventilation.

Protective Gloves: Use Natural rubber or neoprene gloves.

Eye Protection:

Use splash proof chemical safety goggles or appropriate full-face respirator. Follow the eye and face protection guideline of 29 CFR 1910.132 and 1910.133. Where there is any possibility that an individual's eyes may be exposed to methanol, an eye wash fountain should be within the immediate work area for emergency use. Contact lenses should not be worn when working with this chemical.

Protective Clothing and Equipment:

Where there is a possibility of exposure of an individual's body to methanol, facilities for quick drenching of the body should be provided within the immediate work area for emergency use. Such individuals should be provided with and required to use impervious clothing.

Hygienic Work Practices:

Wash with soap and water before eating, drinking, smoking or using toilet facilities. Launder contaminated clothing before using again.

SECTION 8 — SPILL OR LEAK PROCEDURES

Steps To Be Taken In Case Material Is Released or Spilled:

Shut off all sources of ignition. No smoking or flares allowed in the spill area. Restrict access to spill area and move unprotected personnel upwind of the area. Keep out of low areas. Allow only trained personnel wearing appropriate protective clothing and self contained respirator in the positive pressure mode in the vicinity of the spill. Do not touch spilled material; stop leak if you can do so without risk. If fire potential exists, cover spill with foam. Prevent methanol from entering water bodies, drains and any sewage collection systems. Methanol will float on water and

SECTION 8 — SPILL OR LEAK PROCEDURES continued

the runoff will present an explosion or fire hazard. For small spills, take up with sand or other non-combustible absorbent material and place into containers for later disposal. Control large spills by diking. Dispose all spill material in accordance with federal, state and local regulations. Methanol spills over the reportable quantity (5,000 lbs.) should be reported to the National Response Center (800) 424-8802.

Waste Disposal Method:

Must be disposed of in accordance with federal, state and local regulations.

CERCLA (Superfund) Reportable Quantity (in lb.): Methanol - 5,000 lbs.

SECTION 9 — SPECIAL PRECAUTIONS

Precautions To Be Taken In Handling and Storage:

Store in a well ventilated place away from sources of ignition, combustibles, oxidizing materials and acid. Store in an area equipped with automatic sprinklers or fire extinguishing system. Large quantities should be stored in metal tanks or drums. Ground and bond material storage contains and all transfer lines to prevent possible ignition from static sparks. Use spark resistant equipment to store methanol. Containers of this material may be hazardous when emptied. Since emptied containers retain product residues, assume emptied containers to have the same hazards as full containers. Wear appropriate protective equipment when handling methanol. Follow all federal, state and local regulations as well as all insurance codes when storing and handling.

Other precautions: Provide suitable training.

Date entered: 11/06/95

Date revised: NEW

Cyclo Industries, LLC provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgement in determining its appropriateness for a particular purpose. Cyclo Industries, LLC makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Cyclo Industries, LLC will not be responsible for damages resulting from use of or reliance upon this information.