

SECTION 3 — HAZARDOUS INGREDIENTS

<u>CAS Reg. No.</u>	<u>Material</u>	<u>Percentage</u>	<u>Exposure Limits</u>
142-82-5	n-Heptane	25 - 45	50 ppm / TWA OSHA
9002-84-0	PTFE Resin	0 - 1	Not available
64742-52-5	Mineral Oil	25 - 45	Not available
1314-13-2	Zinc Oxide	1 - 10	Not available
68309-87-5	Calcium Thickener	1 - 10	Not available
4485-12-5	Lithium Thickener	0 - 5	Not applicable
68476-86-8	Isobutane/propane	15 - 25	1000 ppm

SECTION 4 — FIRE AND EXPLOSION HAZARD DATA

Flash Point: Less than -20°F

Method Used: T.C.C.

Extinguishing Media: Chemical, foam, carbon dioxide

Special Fire Fighting Equipment: The use of self-contained breathing apparatus is recommended for fire fighters. Water may be unsuitable as an extinguishing media, but helpful in keeping adjacent containers cool. Avoid spreading burning liquid with water used for cooling purposes.

Unusual Fire and Explosion Hazards: Prolonged exposure to temperatures greater than 130EF may cause bursting.

SECTION 5 — HEALTH HAZARD DATA

Effects of Overexposure:

Ingestion: May be harmful or fatal. Call a physician.

Inhalation: May cause breathing difficulties.

Skin Contact: May cause irritation.

Eye Contact: May cause irritation.

First Aid Procedures:

Ingestion: Contact a physician immediately. Do not induce vomiting.

Skin Contact: Wash skin with soap and water.

Inhalation: Remove to fresh air. Administer oxygen if needed.

Eye Contact: Flush with plenty of water for at least 15 minutes. If irritation persists, call a physician.

SECTION 6 — REACTIVITY DATA

Stability: Stable

Conditions to Avoid: Temperatures above 130EF.

Incompatibility (materials to avoid): None known.

SECTION 6 — REACTIVITY DATA continued

Hazardous Decomposition Products: None known.

Hazardous Polymerization: Will not occur.

SECTION 7 — SPECIAL PROTECTION INFORMATION

Respiratory Protection: Not normally required.

Ventilation:

Local Exhaust Rate: Recommended Special: None
Mechanical (General): Acceptable

Protective Gloves: Rubber gloves. Eye Protection: Safety glasses.

Other Protective Equipment: None under normal use; however, use of solvent resistant aprons or other clothing is recommended.

Work/Hygienic Practices: Eye washes and safety showers in the workplace are recommended.

SECTION 8 — SPILL OR LEAK PROCEDURES

Steps To Be Taken In Case Material Is Released or Spilled: Pick up excess with absorbent material and discard in accordance with regulations.

Waste Disposal Method: In accordance with local, state and federal regulations.

SECTION 9 — SPECIAL PRECAUTIONS

Precautions To Be Taken In Handling and Storage: Contents under pressure. Do not store below 32°F or above 130°F. Do not puncture or incinerate. Do not use or store near heat, sparks or open flame. Keep this and all chemicals out of the reach of children. Recommend use with ventilation.

Date entered: 7/21/95

Date revised: 12/07/01

Cyclo Industries, LLC provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgement in determining its appropriateness for a particular purpose. Cyclo Industries, LLC makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Cyclo Industries, LLC will not be responsible for damages resulting from use of or reliance upon this information.