



CYCLO[®] INDUSTRIES, LLC

MATERIAL SAFETY DATA SHEET

This MSDS is being provided to your company for the purpose of providing current health and safety information to your management and for your employees who work with this product. Please read the information on these sheets and then provide this information to those people at your company whose responsibility it is to comply with FEDERAL, STATE and COMMUNITY RIGHT TO KNOW regulations. Also, make this information available to any employee who requests it.

If Cyclo Industries, LLC considers the formula of this product to be a trade secret, the exact chemical names of the ingredient(s) and the percentages in which they are combined will not appear in the body of this sheet. The exact composition is available upon request to physicians, industrial hygienists and other health professionals.

SECTION 1 – PRODUCT & COMPANY IDENTIFICATION

Product Name: Cyclo[®] GREY^oOXTM Silicone Instant RTV Gasket Maker, Stock No. C-979
 Cyclo[®] BLACK^oOXTM Silicone Instant RTV Gasket Maker, Stock No. C-981

Product Use: Gasket replacement or coating gaskets for valve covers, water pumps, thermostat housings, etc.

Manufactured by: Cyclo Industries, LLC
 10190 Riverside Drive, Palm Beach Gardens, Florida 33410-4881
 Telephone: (561) 775-9600

First Aid Emergency: (800) 752-7869 or (312) 906-6194
Shipping Emergency: (800) 424-9300 or (703) 527-3887 (CHEMTREC)

SECTION 2 – COMPOSITION/INFORMATION ON INGREDIENTS

CAS Reg. No.	Material	Percentage	Exposure Limits
22984-54-9	Methyl tris (methylethylketoxime) silane	1 – 5	See methylethylketoxime comments
2224-33-1	Vinyl tris (methylethylketoxime) silane	0.1 – 1	See methylethylketoxime comments
7631-86-9	Silica, amorphous	1 – 5	20 ppm TWA = OSHA PEL 80 mg/m ³ TWA = OSHA PEL 6 mg/m ³ TWA = NIOSH *** See comments below
1317-65-3	Calcium Carbonate (Limestone)	30 – 60	* 15/5 mg/m ³ TWA = OSHA * 10/5 mg/m ³ TWA = NIOSH ** 10 mg/m ³ TWA = ACGIH *** See comments below

* Respirable mass / Total mass respectively.
 ** ACGIH – Inhalable (total) particulate matter containing no asbestos and <1% crystalline silica.
 *** Under normal conditions of use no respirable silica particles should be released from this product. As a by-product of cure up to 4% methylethylketoxime (MEKO, CAS #96-29-7) is formed on contact with water or humid air.
 Provide adequate ventilation to control exposures within the following guidelines: TWA – 3ppm; STEL – 10 ppm AIHA WEEL TWA – 10ppm.

SECTION 3 – HAZARDS IDENTIFICATION

Effects of Overexposure:

- Ingestion: Small amounts transferred to the mouth by fingers during use, etc. should not injure. Swallowing large amounts may injure slightly.
- Inhalation: Vapor overexposure may cause drowsiness, injure blood, liver and may irritate eyes, nose and throat.
- Skin Contact: A single short exposure (less than 24 hours) may irritate. Repeated prolonged contact (24 to 48 hours may irritate moderately. Product contains oximes which are possible skin sensitizers.
- Eye Contact: Direct contact irritates slightly with redness and swelling.

Carcinogenicity: NTP Carcinogen = No; IARC Monographs = No; OSHA Regulated = No

Special Hazards: This material contains the following components with the special hazards listed below:

- | | |
|-------------------------|---------------------------------|
| Carcinogens: None known | Teratogens: None known |
| Mutagens: None known | Reproductive toxins: None known |
| Sensitizers: | |

<u>CAS #</u>	<u>Ingredient</u>	<u>Wt. %</u>	
22984-54-9	Methyl tris (methylethylketoxime) silane	1-7	Possible skin sensitizer
2224-33-1	Vinyl tris (methylethylketoxime) silane	0-1	Possible skin sensitizer

Comments: Methylethylketoxime (MEKO, CAS #96-29-7) is formed upon contact with water or humid air. Male rodents exposed to MEKO vapor throughout their lifetime developed liver cancer. Additional testing is planned by the MEKO supplier to determine any relevance to humans. Until more data is known, exposure levels should be maintained as low as achievable.

This product contains polydimethylsiloxane (silicone) and when heated to temperatures above 302°F /150°C in the presence of air, silicones can form formaldehyde vapors. Formaldehyde is a potential cancer hazard, a known skin and respiratory sensitizer, and an irritant to the eyes, nose, throat, skin and digestive system. Safe handling conditions may be maintained by keeping vapor concentrations within the OSHA permissible exposure limit for formaldehyde.

The above listed potential effects of overexposure are based on actual data, results of studies performed on similar compositions, component data and/or expert review of the product. Overexposure to any chemical may result in enhancement of preexisting adverse medical conditions and allergic reactions.

SECTION 4 – FIRST AID MEASURES

First Aid Procedures:

- Ingestion: Get medical attention.
- Skin Contact: Remove from skin and immediately flush with water for 15 minutes. Get medical attention if irritation develops or ill effects persist.
- Inhalation: Remove to fresh air. If ill effects persist, get medical attention.
- Eye Contact: Immediately flush with water for 15 minutes. Get medical attention.

SECTION 5 – FIRE FIGHTING MEASURES

Flash Point: Not applicable (solid)

Autoignition Temperature: Not determined

Flammable Limits in Air by Volume:

Lower Explosion Level (LEL) = Not determined

Upper Explosion Level (UEL) = Not determined

Extinguishing Media: On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO₂), dry chemical or water spray. Water can be used to cool fire exposed containers.

Special Fire Fighting Procedures: Self-contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

Unusual Fire and Explosion Hazards: None

HMIS Code: Health = 1 Flammability = 1 Reactivity = 0

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Spill/Leak Procedures: Use full face SCBA respirator. Avoid eye and skin contact. Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since some silicone materials may present a slip hazard. Final cleaning may require use of steam, solvents or detergents.

SECTION 7 – HANDLING AND STORAGE

Handling Procedures: Use with adequate ventilation. See product label for additional information. KEEP OUT OF THE REACH OF CHILDREN.

Storage Procedures: Keep container closed and store away from water or moisture.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory Protection: Use self-contained breathing apparatus (SCBA) or other supplied-air respirator unless adequate local exhaust ventilation is provided or air sampling data show exposures are within recommended exposure guidelines.

Ventilation: Local Exhaust Rate: Recommended

Mechanical (General): Recommended

Protective Gloves: Silver Shield[®], 4h[®], butyl rubber, natural rubber, neoprene rubber and nitrile rubber.

Eye Protection: Use safety glasses.

Other Protective Equipment: Wash at mealtimes and end of shift. If skin contact occurs, change contaminated clothing as soon as possible and thoroughly flush effected areas with cool water. Chemical protective gloves are recommended.

Work/Hygienic Practices: Eye washes and safety showers in the workplace are recommended.

SECTION 14 – TRANSPORT INFORMATION

U.S. DOT

Shipping Description:	Aerosols, Consumer Commodity ORM-D
ID Number:	Not applicable
Hazard Class:	Not applicable
Packing Group:	Not applicable
Label:	Not applicable
Placards:	Not applicable

IMDG

Shipping Description:	Aerosols, Limited Quantity
ID Number:	UN 1950
Hazard Class:	2
Packing Group:	Not applicable
Label:	Not applicable
Markings:	Limited Quantity
Placards:	Not applicable

SECTION 15 – REGULATORY INFORMATION

TSCA Inventory: All components of this product are listed on the Toxic Substance Control Act (TSCA) Inventory of chemical substances maintained by the U.S. Environmental Protection Agency.

SARA Extremely Hazardous Substances None

SARA Section 313 This product contains the following toxic chemical subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372 (SARA 313 – Toxic Chemical Release Reporting)

<u>Chemical Name</u>	<u>CAS#</u>	<u>Weight %</u>
None		

CERCLA/Superfund (RQ): This product is not subject to CERCLA reporting requirements. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

California Proposition 65: This product does not contain chemicals known to the State of California to cause cancer, birth defects and other reproductive harm.

SECTION 16 – OTHER INFORMATION

Document Date: September 8, 2003

Supersedes: April 17, 2002

Revisions: Added Sections 11, 12 and 15

Cyclo Industries, LLC provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgement in determining its appropriateness for a particular purpose. Cyclo Industries, LLC makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Cyclo Industries, LLC will not be responsible for damages resulting from use of or reliance upon this information.