



CYCLO[®] INDUSTRIES, LLC

MATERIAL SAFETY DATA SHEET

This MSDS is being provided to your company for the purpose of providing current health and safety information to your management and for your employees who work with this product. Please read the information on these sheets and then provide this information to those people at your company whose responsibility it is to comply with FEDERAL, STATE and COMMUNITY RIGHT TO KNOW regulations. Also, make this information available to any employee who requests it.

If Cyclo Industries, LLC considers the formula of this product to be a trade secret, the exact chemical names of the ingredient(s) and the percentages in which they are combined will not appear in the body of this sheet. The exact composition is available upon request to physicians, industrial hygienists and other health professionals.

SECTION 1 – PRODUCT & COMPANY IDENTIFICATION

Product Name: Cyclo[®] *Fast Start*[®] Starting Fluid, Stock Nos. C-99 & C-100

Product Use: High ether formula engine starting fluid for gasoline and diesel engines. Contains upper cylinder lubricant and rust inhibitor. Fast cold weather starts to –65°F

Manufactured by: Cyclo Industries, LLC
10190 Riverside Drive, Palm Beach Gardens, Florida 33410-4881
Telephone: (561) 775-9600

First Aid Emergency: (800) 752-7869 or (312) 906-6194

Shipping Emergency: (800) 424-9300 or (703) 527-3887 (CHEMTREC)

SECTION 2 – COMPOSITION/INFORMATION ON INGREDIENTS

CAS Reg. No.	Material	Percentage	Exposure Limits
142-82-5	Heptane	60 – 70	500 ppm OSHA
60-29-7	Diethyl ether	25 – 35	400 ppm OSHA
142-38-9	Carbon dioxide	1 – 10	5000 ppm OSHA
N/A	Upper cylinder lubricant	0 – 5	Not established

SECTION 3 – HAZARDS IDENTIFICATION

Effects of Overexposure:

- Ingestion: May cause irritation of throat and stomach
- Inhalation: Headache, dizziness, nausea and loss of consciousness
- Skin Contact: May cause irritation of the skin
- Eye Contact: May cause eye irritation

SECTION 3 – HAZARDS IDENTIFICATION continued

Carcinogenicity: NTP Carcinogen = No; IARC Monographs = No; OSHA Regulated = No

SECTION 4 – FIRST AID MEASURES

First Aid Procedures:

- Ingestion: Do not induce vomiting. Seek medical attention.
- Skin Contact: Remove contaminated clothing and wash with soap and water.
- Inhalation: Remove to fresh air. If breathing has stopped, give artificial respiration.
- Eye Contact: Flush eyes with water for 15 minutes. Seek medical attention if symptoms persist.

SECTION 5 – FIRE FIGHTING MEASURES

Flash Point: -49°F (-45°C)

Method Used: T. C.C.

Extinguishing Media: CO₂, dry chemical, water, fog

Special Fire Fighting Procedures: Handle as extremely flammable liquid. Do not enter confined fire space without helmet, face shield, bunker coat, gloves, rubber boots and a NIOSH-approved self-contained breathing apparatus with full face piece.

Unusual Fire and Explosion Hazards: Containers exposed to intense heat from fires should be cooled with water to prevent pressure buildup which could result in container rupture. Containers that are exposed to direct flame should be cooled with water to eliminate structural weakening of the container's wall and possible rupture.

HMIS Code: Health = 2

Flammability = 4

Reactivity = 1

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Spill/Leak Procedures: Ventilate area, remove sources of ignition, prevent entry into sewers, pick up free liquid with inert absorbent material for proper disposal.

SECTION 7 – HANDLING AND STORAGE

Handling Procedures: Contents under pressure. Do not puncture or incinerate. Prolonged exposure of cans to elevated temperatures may cause cans to vent, rupture or burst. See product label for additional information. KEEP OUT OF THE REACH OF CHILDREN.

Storage Procedures: Store cans in a cool, dry, ventilated area away from ignition sources. Do not store above 120°F (50°C).

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory Protection: Use NIOSH/OSHA approved respirator if ventilation is inadequate.

Ventilation: Sufficient to prevent inhalation of solvent vapors. General dilution and/or local exhaust ventilation in volume or pattern to keep PEL/TLV of most hazardous ingredient below acceptable limit and LEL below stated limit.

Protective Gloves: Neoprene type required for prolonged or repeated contact.

Eye Protection: Safety glasses with splash guards or full face shield is recommended.

Other Protective Equipment: None

Work/Hygienic Practices: Eye washes and safety showers in the workplace are recommended.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: 95°F (35°C)

Specific Gravity (H₂O=1): 0.713

Vapor Pressure: 537

Vapor Density: 2.55

Solubility in Water: Slight

pH: Not determined

Percent Volatile By Volume (%): Not determined

Evaporation Rate (Butyl Acetate = 1): 37.5

Appearance and Odor: Clear liquid with ethereal odor

Volatile Organic Compound (VOC) (as packaged minus water): 93%

SECTION 10 – STABILITY AND REACTIVITY

Stability: Stable

Conditions to Avoid: Keep away from heat, sparks or open flames. Do not store above 120°F (50°C).

Incompatibility (materials to avoid): Strong oxidizing agents.

Hazardous Decomposition or Byproducts: Smoke, carbon monoxide and carbon dioxide.

Hazardous Polymerization: Will not occur.

SECTION 11 – TOXICOLOGICAL INFORMATION

Long-term toxicological studies have not been conducted for this product. See Section 3 of this MSDS for acute symptoms of overexposure and carcinogenicity information.

SECTION 12 – ECOLOGICAL INFORMATION

Aquatic/Terrestrial Toxicity Environmental Fate No data is available at this time.

SECTION 13 – DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in accordance with local, state and federal regulations. Before attempting clean up, refer to other sections of this MSDS for hazard caution information.

SECTION 14 – TRANSPORT INFORMATION**U.S. DOT****Shipping**

Description: Consumer Commodity ORM-D
ID Number: Not applicable
Hazard Class: Not applicable
Packing Group: Not required
Label: Not required
Markings: Not required
Placards: Not required

IMDG**Shipping**

Description: Aerosols, Ltd. Qty.
ID Number: UN 1950
Hazard Class: 2
Packing Group: Not applicable
Label: Not required
Markings: Not required
Placards: Not required

SECTION 15 – REGULATORY INFORMATION

TSCA Inventory: All components of this product are listed on the Toxic Substance Control Act (TSCA) Inventory of chemical substances maintained by the U.S. Environmental Protection Agency.

SARA Extremely Hazardous Substances None

SARA Section 313 This product contains the following toxic chemical subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372 (SARA 313 – Toxic Chemical Release Reporting)

<u>Chemical Name</u>	<u>CAS#</u>	<u>Weight %</u>
None		

<u>CERCLA/Superfund (RQ):</u>	<u>Chemical Name</u>	<u>CAS#</u>	<u>RQ(lbs.)</u>
	Diethyl ether	60-29-7	100

SECTION 15 – REGULATORY INFORMATION

California Proposition 65: This product does not contain chemicals known to the State of California to cause cancer, birth defects and other reproductive harm.

SECTION 16 – OTHER INFORMATION

Document Date: 8/4/03

Supersedes: 1/7/00

Revisions: Added Sections 11, 12 and 15

Cyclo Industries, LLC provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgement in determining its appropriateness for a particular purpose. Cyclo Industries, LLC makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Cyclo Industries, LLC will not be responsible for damages resulting from use of or reliance upon this information.