

CYCLO[®] INDUSTRIES, LLC

MATERIAL SAFETY DATA SHEET

10190 Riverside Drive, Palm Beach Gardens, Florida 33410-4881

Phone: (561) 775-9600

First Aid Emergency: (800) 752-7869 Ext. 10 or (312) 906-6194 Ext. 10

Shipping Emergency: (800) 424-9300 or (703) 527-3887

This MSDS is being provided to your company for the purpose of providing current health and safety information to your management and for your employees who work with this product. Please read the information on these sheets and then provide this information to those people at your company whose responsibility it is to comply with FEDERAL, STATE and COMMUNITY RIGHT TO KNOW regulations. Also, make this information available to any employee who requests it.

If Cyclo Industries, LLC considers the formula of this product to be a trade secret, the exact chemical names of the ingredient(s) and the percentages in which they are combined will not appear in the body of this sheet. The exact composition is available upon request to physicians, industrial hygienists and other health professionals.

SECTION 1 - PRODUCT IDENTIFICATION

Product Name: 82116 Rally[®] Cream Car Wax

Hazardous Material Description:

DOT = Cleaners, Polishes, Waxes, Consumer Commodity ORM-D

IMDG = Flammable Liquid, N.O.S. (Contains Petroleum Distillates), Class 3, UN1993, III, Limited Quantity

SECTION 2 - PHYSICAL DATA

Specific Gravity (H₂O=1): 0.94 – 0.98 @ 25°C

Solubility in Water: Very slightly soluble

Evaporation Rate (Butyl Acetate = 1): <1.0 @ 25°C

pH: ~9.0

Appearance and Odor: Off-white cream paste with slight solvent odor.

SECTION 3 - HAZARDOUS INGREDIENTS

<u>CAS Reg. No.</u>	<u>Material</u>	<u>Percentage</u>	<u>Exposure Limits</u>
N/A	Petroleum distillates	40 – 60	100 ppm TLV / TWA*
66402-68-4	Calcined kaolin clay	10 – 30	2 mg/m ³ TLV / TWA 15 mg/m ³ OSHA PEL
107-21-1	Ethylene glycol	1 – 5	Not established

* Based on ACGIH TLV-TWA for stoddard solvent.

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

Flash Point: 106°F / 41°C

Method Used: Tagliabue Closed Cup

Extinguishing Media: Water, water fog, dry chemical, foam or carbon dioxide (CO₂).

Special Fire Fighting Procedures: Do not use a direct stream of water.

Unusual Fire and Explosion Hazards: COMBUSTIBLE. Slightly flammable to flammable in the presence of heat.

SECTION 5 - HEALTH HAZARD DATA

Effects of Overexposure:

Inhalation: Repeated or prolonged exposure to solvent concentrations above the Worker Exposure Limit may cause central nervous system depression (e.g. dizziness, weakness, nausea, headaches and/or unconsciousness). Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage.

Skin Contact: Repeated or prolonged contact may cause skin irritation.

Eye Contact: May cause eye irritation.

Carcinogenicity: NTP Carcinogen = No; IARC Monographs = No; OSHA Regulated = No

First Aid Procedures:

Ingestion: Drink a glassful of water. Get prompt medical attention.

Skin Contact: Wash area with soap and water. If irritation persists, get medical attention.

Inhalation: Remove to fresh air. If breathing problems or irritation persist, get medical attention.

Eye Contact: Remove contact lenses. Immediately flush eyes thoroughly with plenty of water for 15 minutes. Get medical attention.

SECTION 6 - REACTIVITY DATA

Stability: Stable under normal use and conditions.

Conditions to Avoid: Strong oxidizing agents.

SECTION 7 - SPECIAL PROTECTION INFORMATION

Respiratory Protection: Use a NIOSH-approved respirator if exposure may exceed occupational exposure limits.

Ventilation: Use local or general ventilation to minimize exposure to vapor.

Protective Gloves: Wear material resistant gloves if handling for prolonged or repeated periods.

SECTION 7 - SPECIAL PROTECTION INFORMATION continued

Eye Protection: Wear safety glasses or goggles

Work/Hygienic Practices: Eye washes and safety showers in the workplace are recommended. Wash hands with soap and water after use. Do not wear product-contaminated clothing for prolonged periods.

SECTION 8 - SPILL OR LEAK PROCEDURES

Steps To Be Taken In Case Material Is Released or Spilled: CAUTION – COMBUSTIBLE. Eliminate potential sources of ignition. Absorb and containerize. Do not wash down sanitary sewer.

Waste Disposal Method: Dispose of in accordance with local, state and federal regulations. Before attempting clean up, refer to other sections of this MSDS for hazard caution information.

SECTION 9 - SPECIAL PRECAUTIONS

Precautions To Be Taken In Handling and Storage: Keep container closed when not in use. Store away from open flames, sparks, heat sources, strong oxidants and corrosives. Do not smoke while using this product.

Other precautions: KEEP OUT OF REACH OF CHILDREN. Avoid eye and skin contact and inhalation of vapor.

SECTION 10 – REGULATORY INFORMATION

TSCA: All ingredients in this product are listed on the TSCA inventory.

EPA – SARA Title III/CERCLA: packaged product is not reportable under Sections 311/312. Product contains the following reportable chemical(s):

Ethylene glycol – SARA 304, SARA 313

Date revised: 3/2/01

Cyclo Industries, LLC provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgement in determining its appropriateness for a particular purpose. Cyclo Industries, LLC makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Cyclo Industries, LLC will not be responsible for damages resulting from use of or reliance upon this information.