



## MATERIAL SAFETY DATA SHEET

350 RING ROAD ELIZABETHTOWN, KY 42701 (270) 769-5557 (270) 769-6418

# RED RTV SILICONE GASKET MAKER HI-TEMP PART NOS. 49202, 49292

### SECTION I - IDENTITY INFORMATION

Description : RTV High Temperature Silicone Gasket  
Maker-Red  
Chemical Family : RTV Silicone

### SECTION II - HAZARDOUS INGREDIENTS

| <u>INGREDIENTS</u>     | <u>CAS NO.</u> | <u>EXPOSURE LIMITS</u>                                      | <u>WGT. %</u> |
|------------------------|----------------|---|---------------|
| Methyltriacetoxysilane | 004253343      | See Comment Below   | 2             |
| Ethyltriacetoxysilane  | 017689779      | See Comment Below   | 2             |
| Silica, Amorphous      | 007631869      | OSHA PEL: TWA 6 MG/M3<br>ACGIH TLV: TWA 10 MG/M3 Total Dust | 10            |

**COMMENT:** *Observe Limits for Acetic Acid, Formed During Curing on Exposure to Water or Humid Air. OSHA PEL: TWA 10 PPM. ACGIH TLV: TWA 10 PPM, STEL 15 PPM.*

### SECTION III - PHYSICAL AND CHEMICAL CHARACTERISTICS

Boiling Point (@ 760 MM HG) : N/A  
Melting Point : N/A  
Vapor Pressure (@ 77°F/25°C) : N/A  
Vapor Density (Air=1 @ 77°F/25°C) : N/A  
Solubility in Water (%) : <1  
Specific Gravity (@ 77°F/25°C) : 1.03  
Percent Volatile by Weight (%) : <5  
Evaporation Rate (Ether=1) : N/A  
Odor, Appearance, Color : Acetic acid-like, paste, red.

### SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used) : Open cup above 250°F/120°C  
Flammability Limits in Air : Lower - N/D Upper - N/D  
Extinguishing Media : Water, water fog, CO<sub>2</sub>, dry chemical, foam.

Special Fire Fighting Procedure : Use self-contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals.

Unusual Fire and Explosion Hazards : None

## SECTION V - HEALTH HAZARD DATA

### EFFECTS OF OVEREXPOSURE:

Eye : Direct contact irritates slightly to moderately with redness and swelling.

Skin : A single short exposure (less than 24 hours) may irritate. Repeated prolonged contact (24 to 48 hours) may irritate moderately.

Inhalation : Vapor overexposure may irritate eyes, nose and throat.

Oral : Small amounts transferred to the mouth by fingers during use, etc. should not injure. Swallowing large amounts may cause digestive discomfort.

### EMERGENCY AND FIRST AID PROCEDURES:

Eyes : Flush eyes immediately with water for at least 15 minutes. Seek medical assistance.

Skin : Scrape off excess, wash with soap and large volumes of water. Get medical attention if irritation develops.

Inhalation : Remove to fresh air. Get medical attention if ill effects persist.

Oral : No first aid should be needed.

## SECTION VI - REACTIVITY DATA

Stability : Stable

Incompatibility (Material to Avoid) : Oxidizing material can cause a reaction. Air or moisture causes curing and acetic acid vapors to form.

Conditions to Avoid : Exposure to air or moisture until ready to use.

Hazardous Decomposition Products : Silicon dioxide, carbon dioxide, and traces of incompletely burned carbon products, includes formaldehyde.

Hazardous Polymerization : Will not occur.

Conditions to Avoid : N/A

## SECTION VII – SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released  
or Spilled : Remove product and contain for salvage or

disposal.

PROTECTIVE EQUIPMENT:

- Eyes : Use proper protection -- safety glasses, as a minimum.
- Skin : Washing at mealtime and end of shift is adequate. Remove contaminated clothing and shoes as soon as practical and clean thoroughly before reuse. Rubber or plastic gloves are recommended
- Inhalation : Use respiratory protection unless local exhaust ventilation is adequate or air sampling data show exposures are within TLV and PEL guidelines.
- Waste Disposal Method : Dispose of in accordance with all local, state and federal regulations concerning health and pollution.

***Comments: Product contains no ingredient subject to D.O.T. or E.P.A CERCLA/SARA Environmental Release Reporting Regulations.***

**SECTION VIII - ROUTINE HANDLING PRECAUTIONS**

PROTECTIVE EQUIPMENT:

- Eyes : Use proper eye protection -- safety glasses, as a minimum.
- Skin\* : Washing at mealtime and end of shift is adequate. Remove contaminated clothing and shoes as soon as practical and clean thoroughly before reuse. Rubber or plastic gloves are recommended
- Inhalation : Use respiratory protection unless local exhaust ventilation is adequate or air sampling data show exposures are within TLV and PEL guidelines.
- VENTILATION:
- Local Exhaust : Recommended.
- Mechanical (General) : Recommended.
- Suitable Respirator : Organic vapor type.

***\*Good Practice requires that Gross Amount of Any Chemical be removed From the Skin As Soon As Practical, Especially before Eating or Smoking.***

***COMMENTS: Avoid Breathing Vapors and Eye and Skin Contact. Use Only with Adequate Ventilation. DO NOT Take Internally.***

**SECTION IX – SPECIAL PRECAUTIONS**

- Precautions to be Taken is Handling and Storing : Store below 90<sup>0</sup>F/32<sup>0</sup>C. Use reasonable care and caution.
- Other Precautions : Product forms acetic acid (HOAC) when ex-

posed to water or humid air. Provide ventilation during use to control HOAC exposure within 10 PPM (current TLV) or use respiratory protection.

**Pg. 4 of 4**  
**P/N's 49202, 49292**

## **SECTION X – REGULATORY INFORMATION**

Proper Shipping Name (49CFR 172.101) : None  
D.O.T. Hazard Name (49CFR 172.101) : None  
D.O.T. ID No. (49CFR 172.101) : None  
D.O.T. Hazard Class (49CFR 172.101) : None  
RCRA Hazard Class (40CFR 261)(if discarded) : None  
E.P.A. Priority Pollutants (40CFR 122.53) : None

## **SECTION XI – HAZARD COMMUNICATION CODES**

### NFPA RATINGS:

Health : 1  
Flammability : 1  
Reactivity : 0

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. Because the information contained herein may be applied under conditions beyond our

control, we assume no responsibility for its use.

**Rev. 2/8/03**