



MATERIAL SAFETY DATA SHEET

350 RING ROAD ELIZABETHTOWN, KY 42701 (270) 769-5557 (270) 769-6418

**GAS TANK REPAIR KIT
PART NO. 49410**

SECTION I - IDENTITY INFORMATION

Trade Name : Fast Cure Epoxy Putty

SECTION II – HAZARDOUS INGREDIENTS

<u>INGREDIENT</u>	<u>CAS NO.</u>	<u>TSCA</u>	<u>HEALTH</u>	<u>FIRE</u>	<u>REACT</u>	<u>P</u>	<u>%</u>
Glycidyl ethers of							
Bisphenol A Resins	25068-18-6	Y	2	1	0	B	10-30
Epoxy Resin	67989-52-0	Y	2	1	0	B	3-7
Zinc Sulfide	1314-98-3	Y	1	0	0	D	1-5
Tri(dimethylaminomethyl)							
Phenol	90-72-2	Y	3	1	1	D	1-5

SECTION III - PHYSICAL DATA

Boiling Range : N/A
Evaporation Rate : 0.0 X n-Butyl Acetate
Volatiles Vol % : 0
Weight % : 0
Vapor Density : Heavier than air.
Liquid Density : Heavier than water.
Weight Per Gallon : 15.20 Pounds
Appearance : Putty-Like

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used) : None (TOC)
LEL : None
UEL : None
Extinguishing Media : Water spray, foam, CO₂, dry chemical.
Special Procedures : None
Unusual Hazards : CO, aldehydes, acids, oxides of sulfur and nitrogen may be formed.

SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:

Inhalation	: None
Ingestion	: Irritation of intestinal tract.
Skin Contact	: Possible irritant and sensitizer.
Eye Contact	: Possible irritant and sensitizer.

FIRST AID:

Inhalation	: N/A
Ingestion	: Induce vomiting.
Skin Contact	: Wash with soap and water.
Eye Contact	: Flush with water. Consult a physician.

SECTION VI - REACTIVITY DATA

Stability	: Stable
Hazardous Polymerization	: Will not occur
Incompatibility	: None
Conditions to Avoid	: None
Hazardous Decomposition Products	: CO, aldehydes, acids, oxides of sulfur and nitrogen.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN:

Spills or Leaks	: Dispose of in normal manner; not a potential pollutant.
Waste Disposal Method	: Incinerate in furnace or bury in landfill according to applicable regulations.

SECTION VIII - PRECAUTION FOR SAFE HANDLING AND USE

PROTECTIVE EQUIPMENT TYPES:

Eyes	: Safety glasses.
Respiratory	: None required.
Gloves	: Polyethylene gloves for prolonged use.
Other	: None required.

VENTILATION:

General Mechanical	: None required.
Local Exhaust	: Only if heated above 100°F (38°C).

PRECAUTIONS:

Handling and Storage	: Avoid eye contact and excessive skin contact.
Other	: Wash with soap and water immediately after use.

SECTION IX – HAZARD COMMUNICATION CODES

HMIS RATINGS:

Health	:	1
Fire	:	0
Reactivity	:	0
Personal Protection	:	E

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. Because the information contained herein may be applied under conditions beyond our control, we assume no responsibility for its use.