

TXL Extra Thin Wall Wire

- Jacket: Cross-linked polyethylene
- Conductor: Stranded, bare copper
- Rated: -40°F to 257°F; 50 volts or less
- Specifications: SAE J1128; Chrysler MS-8288; Ford ESB-M1L123A
- Features: Conforms to tight areas
- Uses: automotive applications where high heat resistance, minimal diameter & weight are required



| Part Number | Stranding | Nom. O.D. (inches) | Bulk Qty. (feet) |
|-------------|-----------|--------------------|------------------|
| 22 TXL | 7 x 30 | .062 | 5000 |
| 20 TXL | 7 x 28 | .070 | 5000 |
| 18 TXL | 19 x 30 | .078 | 5000 |
| 16 TXL | 19 x 29 | .089 | 5000 |
| 14 TXL | 19 x 27 | .103 | 5000 |
| 12 TXL | 19 x 25 | .124 | 2500 |
| 10 TXL | 19 x 23 | .155 | 1000 |

| Colors | | | | Spool Sizes | |
|-----------|-----|--------|-----|-------------|------|
| Black | BLK | Orange | ORG | 100ft. | 100 |
| Blue | BLU | Pink | PNK | 500ft. | 500 |
| Brown | BRN | Purple | PUR | 1000ft. | 1000 |
| Gray | GRY | Red | RED | Bulk Reel | BULK |
| Green | GRN | Tan | TAN | | |
| Lt. Blue | LBL | White | WHT | | |
| Lt. Green | LGR | Yellow | YEL | | |

For the correct part number, use the abbreviations above (in red), along with this example:

16 TXL - 1000 - YEL

Tefzel High Temp Wire

- Jacket: Extruded teflon
- Conductor: Stranded, silver-plated copper
- Rated: -67°F to 392°F; 600 volts
- Specifications: SAE AS22759
- Features: Resistant to high temperatures where smoke emission, overload stability & flammability may be a problem
- Uses: for racing teams or in any other application where high heat resistance is a must



| Part Number | Stranding | Nom. O.D. (inches) | Colors Available |
|-------------|-----------|--------------------|--------------------|
| 20 TEF | 19 x 32 | .068 | RED, BLK |
| 18 TEF | 19 x 30 | .078 | BLK, RED, WHT, YEL |
| 16 TEF | 19 x 29 | .085 | |
| 14 TEF | 19 x 27 | .100 | BLK, ORG, RED |
| 12 TEF | 19 x 25 | .120 | BLK, RED, WHT |

| Colors* | | | | Spool Sizes | |
|---------|-----|--------|-----|-------------|------|
| Black | BLK | White | WHT | 100ft. | 100 |
| Orange | ORG | Yellow | YEL | 500ft. | 500 |
| Red | RED | | | 1000ft. | 1000 |

For the correct part number, use the abbreviations above (in red), along with this example:

20 TEF - 500 - RED

Minimums may apply on some colors & sizes

Specialty Wire Services

Are you interested in having your wire pre-cut, stripped or even terminated? Our in-house wire capabilities can help you finish your next project quickly & to your exact specifications. We also offer striped wire in almost any combination of our standard colors. Talk to your sales rep or customer service for more information on these services & more!

